

*Tripod Systems for  
Lightweight Cameras*



# **MARK-Series & DV6P**

*75 mm bowls*



# Camgear MARK Lite

**Payload 6KG Bowl 75MM**



## Specifications

Model Number	MARK Lite
Maximum Payload	6 kg/ 13.2 lbs
Camera Platform Type	Sliding camera plate (Camgear SP-MARK)
Sliding Range	104 mm/4.1 in
Camera Plate	1/4", 3/8" screw & pin
Counterbalance System	On/Off
Pan & Tilt Drag	Fixed
Pan & Tilt Range	Pan: 360° / Tilt: +90°/-75°
Temperature Range	-40°C to +60°C / -40 to +140°F
Levelling Bubble	Yes
Weight	1.42 kg/ 3.13 lbs
Bowl Diameter	75 mm

- ◆ Real professional drag performance offer operators silky smooth movement and precise framing.
- ◆ On/Off counterbalance system gives users more options than fixed counterbalance.
- ◆ With levelling bubble.
- ◆ Ideal for DSLR configuration and lightweight camcorders.
- ◆ Spare camera screws are placed on head.
- ◆ 75 mm ball levelling, which can be converted to flat base.

## Camgear MARK Lite GS CF Bowl 75MM

Tripod System incl. MARK Lite Fluid Head, Carbon Fiber Tripod & Ground Spreader.

SKU: CMG-MLITE-GS-CF-TRISYS

### System Configuration

MARK Lite Fluid Head  
MARK CF/GS2 2-Stage  
Carbon Fiber Tripod  
PB-MARK Pan Bar  
GS-MARK Ground Spreader  
Tripod Bag



Weight	4.1 kg/9 lbs
Height Range	0.57-1.74 m/22.4-68.5 in
Transport Length	0.87 m/34.2 in
Section	2 Stages

## Camgear MARK Lite GS AL Bowl 75MM

Tripod System incl. MARK Lite Fluid Head, Aluminum Tripod & Ground Spreader.

SKU: CMG-MLITE-GS-AL-TRISYS

### System Configuration

MARK Lite Fluid Head  
MARK AL/GS2 2-Stage  
Aluminum Tripod  
PB-MARK Pan Bar  
GS-MARK Ground Spreader  
Tripod Bag



Weight	4.7 kg/10.36 lbs
Height Range	0.57-1.74 m/22.4-68.5 in
Transport Length	0.87 m/34.2 in
Section	2 Stages

## Camgear MARK Lite MS CF Bowl 75MM

Tripod System incl. MARK Lite Fluid Head, Carbon Fiber Tripod & Mid Level Spreader.

SKU: CMG-MLITE-MS-CF-TRISYS

### System Configuration

MARK Lite Fluid Head  
MARK CF/MS2 2-Stage  
Carbon Fiber Tripod  
PB-MARK Pan Bar  
Mid Level Spreader  
Tripod Bag



Weight	3.9 kg/8.6 lbs
Height Range	0.79-1.69 m/31.1-66.5 in
Transport Length	0.84 m/33 in
Section	2 Stages

## Camgear MARK Lite MS AL Bowl 75MM

Tripod System incl. MARK Lite Fluid Head, Aluminum Tripod & Mid Level Spreader.

SKU: CMG-MLITE-MS-AL-TRISYS

### System Configuration

MARK Lite Fluid Head  
MARK AL/MS2 2-Stage  
Aluminum Tripod  
PB-MARK Pan Bar  
Mid Level Spreader  
Tripod Bag



Weight	4.5 kg/9.92 lbs
Height Range	0.79-1.69 m/31.1-66.5 in
Transport Length	0.84 m/33 in
Section	2 Stages

Camgear MARK 4

Payload 7KG


Bowl 75MM



Specifications

Model Number	MARK 4
Maximum Payload	7 kg/15.4 lbs
Counterbalance Range	0-7 kg/0-15.4 lbs (at C.O.G 50 mm)
Camera Platform Type	Sliding camera plate (Camgear SP-MARK)
Sliding Range	104 mm/4.1 in
Camera Plate	1/4", 3/8" screw & pin
Counterbalance System	6 steps (1-6)
Pan & Tilt Drag	4 steps (1-4)
Pan & Tilt Range	Pan: 360° / Tilt: +90°/-75°
Temperature Range	-40°C to +60°C / -40 to +140°F
Levelling Bubble	Yes
Weight	1.42 kg/3.13 lbs
Bowl Diameter	75 mm

- ◆ Real professional drag performance, selectable 4 positions pan & tilt drag including zero position, offer operators silky smooth movement and precise framing.
- ◆ Selectable 6 position counterbalance system including zero position for up to 7 kg/15.4 lbs payload.
- ◆ With levelling bubble.
- ◆ Ideal for DSLR configuration and lightweight camcorders.
- ◆ Spare camera screws are placed on head.
- ◆ 75 mm ball levelling, which can be converted to flat base.



Camgear MARK 4 GS CF

Bowl 75MM

Tripod System incl. MARK 4 Fluid Head, Carbon Fiber Tripod & Ground Spreader.

SKU: CMG-M4-GS-CF-TRISYS

System Configuration

- MARK 4 Fluid Head
- MARK CF/GS2 2-Stage
- Carbon Fiber Tripod
- PB-MARK Pan Bar
- GS-MARK Ground Spreader
- Tripod Bag



Weight	4.1 kg/9 lbs
Height Range	0.57-1.74 m/22.4-68.5 in
Transport Length	0.87 m/34.2 in
Section	2 Stages

Camgear MARK 4 GS AL

Bowl 75MM

Tripod System incl. MARK 4 Fluid Head, Aluminum Tripod & Ground Spreader.

SKU: CMG-M4-GS-AL-TRISYS

System Configuration

- MARK 4 Fluid Head
- MARK AL/GS2 2-Stage
- Aluminum Tripod
- PB-MARK Pan Bar
- GS-MARK Ground Spreader
- Tripod Bag



Weight	4.7 kg/10.36 lbs
Height Range	0.57-1.74 m/22.4-68.5 in
Transport Length	0.87 m/34.2 in
Section	2 Stages

Camgear MARK 4 MS CF

Bowl 75MM

Tripod System incl. MARK 4 Fluid Head, Carbon Fiber Tripod & Mid Level Spreader.

SKU: CMG-M4-MS-CF-TRISYS

System Configuration

- MARK 4 Fluid Head
- MARK CF/MS2 2-Stage
- Carbon Fiber Tripod
- PB-MARK Pan Bar
- MSP-MARK Mid Level Spreader
- RF-MARK Rubber Feet (x3)
- Tripod Bag



Weight	3.9 kg/8.6 lbs
Height Range	0.79-1.69 m/31.1-66.5 in
Transport Length	0.84 m/33 in
Section	2 Stages

Camgear MARK 4 MS AL

Bowl 75MM

Tripod System incl. MARK 4 Fluid Head, Aluminum Tripod & Mid Level Spreader.

SKU: CMG-M4-MS-AL-TRISYS

System Configuration

- MARK 4 Fluid Head
- MARK AL/MS2 2-Stage
- Aluminum Tripod
- PB-MARK Pan Bar
- MSP-MARK Mid Level Spreader
- RF-MARK Rubber Feet (x3)
- Tripod Bag



Weight	4.5 kg/9.92 lbs
Height Range	0.79-1.69 m/31.1-66.5 in
Transport Length	0.84 m/33 in
Section	2 Stages

# Camgear MARK 6

Payload 10KG


Bowl 75MM



## Specifications

Model Number	MARK 6
Maximum Payload	10 kg/22 lbs
Counterbalance Range	0-10 kg/0-22 lbs (at C.O.G 50 mm)
Camera Platform Type	Sliding camera plate (Camgear SP-MARK)
Sliding Range	104 mm/4.1 in
Camera Plate	1/4", 3/8" screw & pin
Counterbalance System	8 steps (1-8)
Pan & Tilt Drag	4 steps (1-4)
Pan & Tilt Range	Pan: 360° / Tilt: +90°/-75°
Temperature Range	-40°C to +60°C / -40 to +140°F
Levelling Bubble	Yes
Weight	1.42 kg/3.13 lbs
Bowl Diameter	75 mm

- ◆ Real professional drag performance, selectable 4 positions pan & tilt drag including zero position, offer operators the silky smooth movement and precise framing.
- ◆ Selectable 8 position counterbalance system including zero position for payloads between 0-10 kg/0-22 lbs.
- ◆ With levelling bubble.
- ◆ Ideal for DSLR configuration and lightweight camcorders.
- ◆ Spare camera screws are placed on head.
- ◆ 75 mm ball levelling, which can be converted to flat base.



## Camgear MARK 6 GS CF Bowl 75MM

Tripod System incl. MARK 6 Fluid Head, Carbon Fiber Tripod & Ground Spreader.

SKU: CMG-M6-GS-CF-TRISYS

### System Configuration

MARK 6 Fluid Head  
MARK CF/GS2 2-Stage  
Carbon Fiber Tripod  
PB-MARK Pan Bar  
GS-MARK Ground Spreader  
Tripod Bag



Weight	4.1 kg/9 lbs
Height Range	0.57-1.74 m/22.4-68.5 in
Transport Length	0.87 m/34.2 in
Section	2 Stages

## Camgear MARK 6 GS AL Bowl 75MM

Tripod System incl. MARK 6 Fluid Head, Aluminum Tripod & Ground Spreader.

SKU: CMG-M6-GS-AL-TRISYS

### System Configuration

MARK 6 Fluid Head  
MARK AL/GS2 2-Stage  
Aluminum Tripod  
PB-MARK Pan Bar  
GS-MARK Ground Spreader  
Tripod Bag



Weight	4.7 kg/10.36 lbs
Height Range	0.57-1.74 m/22.4-68.5 in
Transport Length	0.87 m/34.2 in
Section	2 Stages

## Camgear MARK 6 MS CF Bowl 75MM

Tripod System incl. MARK 6 Fluid Head, Carbon Fiber Tripod & Mid Level Spreader.

SKU: CMG-M6-MS-CF-TRISYS

### System Configuration

MARK 6 Fluid Head  
MARK CF/MS2 2-Stage  
Carbon Fiber Tripod  
PB-MARK Pan Bar  
MSP-MARK Mid Level Spreader  
RF-MARK Rubber Feet (x3)  
Tripod Bag



Weight	3.9 kg/8.6 lbs
Height Range	0.79-1.69 m/31.1-66.5 in
Transport Length	0.84 m/33 in
Section	2 Stages

## Camgear MARK 6 MS AL Bowl 75MM

Tripod System incl. MARK 6 Fluid Head, Aluminum Tripod & Mid Level Spreader.

SKU: CMG-M6-MS-AL-TRISYS

### System Configuration

MARK 6 Fluid Head  
MARK AL/MS2 2-Stage  
Aluminum Tripod  
PB-MARK Pan Bar  
MSP-MARK Mid Level Spreader  
RF-MARK Rubber Feet (x3)  
Tripod Bag



Weight	4.5 kg/9.92 lbs
Height Range	0.79-1.69 m/31.1-66.5 in
Transport Length	0.84 m/33 in
Section	2 Stages



Camgear DV6P

Payload 10KG


Bowl 75MM



Specifications

Model Number	DV6P
Maximum Payload	10 kg/22 lbs
Counterbalance Range	0-9 kg/0-19.8 lbs (at C.O.G 50 mm)
Camera Platform Type	Mini Euro plate (Camgear WP-2)
Sliding Range	60 mm/2.36 in
Camera Plate	1/4" screw & pin
Counterbalance System	8 steps (1-8)
Pan & Tilt Drag	4 steps (1-4)
Pan & Tilt Range	Pan: 360° / Tilt: +90/-75°
Temperature Range	-40°C to +60°C / -40 to +140°F
Levelling Bubble	Yes
Weight	2.2 kg/4.85 lbs
Bowl Diameter	75 mm

- ◆ Real professional drag performance, selectable 4 positions pan & tilt drag including zero position, offer operators silky smooth movement and precise framing and ensure fast change of drag.
- ◆ Selectable 8 position counterbalance system including zero position gives the operator much fine adjustment for the cameras.
- ◆ With levelling bubble.
- ◆ Ideal for DSLR configuration and lightweight camcorders.
- ◆ 75 mm ball levelling, which can be converted to flat base.
- ◆ Equipped with mini Euro plate quick-release system, which enables faster set-up of camera.



Camgear DV6P GS CF

Bowl 75MM

Tripod System incl. DV6P Fluid Head, Carbon Fiber Tripod & Ground Spreader.

SKU: CMG-DV6P-GS-CF-TRISYS

System Configuration

- DV6P Fluid Head
- T75/CF2 2-Stage
- Carbon Fiber Tripod
- PB-1 Pan Bar
- GS-2 Ground Spreader
- Tripod Bag



Weight	5.90 kg/13.0 lbs
Height Range	0.55-1.64 m/21.7-64.6 in
Transport Length	0.85 m/33.5 in
Section	2 Stages

Camgear DV6P GS AL

Bowl 75MM

Tripod System incl. DV6P Fluid Head, Aluminum Tripod & Ground Spreader.

SKU: CMG-DV6P-GS-AL-TRISYS

System Configuration

- DV6P Fluid Head
- T75/AL2 2-Stage
- Aluminum Tripod
- PB-1 Pan Bar
- GS-2 Ground Spreader
- Tripod Bag



Weight	6.72 kg/14.8 lbs
Height Range	0.55-1.64 m/21.7-64.6 in
Transport Length	0.85 m/33.5 in
Section	2 Stages

Camgear DV6P MS CF

Bowl 75MM

Tripod System incl. DV6P Fluid Head, Carbon Fiber Tripod & Mid Level Spreader.

SKU: CMG-DV6P-MS-CF-TRISYS

System Configuration

- DV6P Fluid Head
- T75/CF2 2-Stage
- Carbon Fiber Tripod
- PB-1 Pan Bar
- MSP-2 Mid Level Spreader
- RF-1 Rubber Feet (x3)
- Tripod Bag



Weight	6.34 kg/14.0 lbs
Height Range	0.64-1.64 m/25.2-64.6 in
Transport Length	0.85 m/33.5 in
Section	2 Stages

Camgear DV6P MS AL

Bowl 75MM

Tripod System incl. DV6P Fluid Head, Aluminum Tripod & Mid Level Spreader.

SKU: CMG-DV6P-MS-AL-TRISYS

System Configuration

- DV6P Fluid Head
- T75/AL2 2-Stage
- Aluminum Tripod
- PB-1 Pan Bar
- MSP-2 Mid Level Spreader
- RF-1 Rubber Feet (x3)
- Tripod Bag



Weight	7.16 kg/15.8 lbs
Height Range	0.64-1.64 m/25.2-64.6 in
Transport Length	0.85 m/33.5 in
Section	2 Stages

# Accessories

## Ground Spreader GS-MARK

For MARK Lite, MARK 4 & MARK 6 Tripod Systems

SKU: CMG-GROUNSPRDR-MARK



**Payload**  
60 kg/132.2 lbs

**Weight**  
0.82 kg/1.83 lbs

**Build-up radius**  
35-60 cm/13-22.8 in

## Dolly S

For MARK 4, MARK 6 & DV6P Tripod Systems

SKU: CMG-DOLLY-S



**Payload**  
35 kg/77.2 lbs

**Dimensions**  
H: 19 cm/H: 7.5 in

**Weight**  
3.32 kg/7.3 lbs

**Build-up radius**  
51 cm/20 in

## Mid Level Spreader MSP-MARK

For MARK 4 & MARK 6 Tripod Systems

SKU: CMG-MIDSPREADER-MARK



**Weight**  
278 g/0.61 lbs

## Rubber Feet RF-MARK (set of 3)

Black Oval Shaped Feet. Required with MARK 4/6 and Mid Level Spreader

SKU: CMG-RUBBERFEET-MARK



**Weight**  
578 g/1.27 lbs

## Pan Bar PB-MARK

For MARK Lite, MARK 4 & MARK 6 Tripod Systems

SKU: CMG-PANBAR-MARK



**Weight**  
240 g/0.53 lbs

**Dimensions**  
37 cm/ 14.6 in

## Sliding Plate SP-MARK

For MARK Lite, MARK 4 & MARK 6 Fluid Heads

SKU: CMG-SLPLATE-MARK



**Weight**  
119 g/0.26 lbs

**Dimensions**  
14 x 5 cm/5.5 x 2 in

## Bowl Clamp BC-MARK

For MARK Lite, MARK 4 & MARK 6 Tripod Systems

SKU: CMG-BOWLCLAMP-MARK



**Weight**  
100 g/0.22 lbs

## Didn't find what you're looking for?

Take a look at our other **tripod ranges**:



### Camgear V-Series

- ◆ Frictionless, stable & reliable performance
- ◆ Graded drag system
- ◆ Counterbalance system for fast set-up and easy operation




### Camgear Elite-Series

- ◆ Patented counterbalance wheel adjustment system
- ◆ Smart storage for screw key and spare screws inside head
- ◆ Elite tripod systems are equipped with our patented 3S-FIX Quick Lock & Release mechanism



For more information about distributors, delivery and service please visit [www.camgear-pro.com](http://www.camgear-pro.com)

YOUR LOCAL RESELLER:



[www.camgear-pro.com](http://www.camgear-pro.com)

This catalog has been compiled with the greatest possible care. However, mistakes or changes in models, designs, specifications, visuals or any other information are under reserve. No rights can be derived in any way from the content of this catalog. Technical additions or errors do not constitute grounds for compensation claims.